




## Wireless Temperature Sensor

Rugged for on-metal applications



### Battery-free equipment monitoring

The AZN3254 is a wireless battery-free temperature sensor. This rugged sensor is designed to switchgear contactor points, busbars and equipment temperatures in the harsh and extreme environments. Other uses include electric motor protection, bearing temperature monitoring, heating and cooling equipment (HVAC) efficiency monitoring and other applications where metal surfaces are common.

### APPLICATIONS

- Switchgear contactor points
- Electric busbar monitoring
- Predictive maintenance
- Monitor electric motors
- Monitor HVAC efficiency
- Monitor AC switchgear

### KEY FEATURES

- Normal temperature range  
-40 °C to +85 °C
- High-temperature alarm up  
to +125 °C
- Powered by Magnus® S3
- Sensor size  
13.5 x 9.1 x 4.3 mm
- Battery-free design
- Adhesive backing

### Wireless temperature sensing

The AZN3254 has a normal operating temperature range of -40 °C to +85 °C. This covers the typical operating temperatures of most equipment over a range of environmental operating conditions. The AZN3254 reports temperatures beyond its normal operating range to as high as +125 °C, although prolonged operation at such an elevated temperature is not recommended.

### Rugged design for use on metal and equipment

The AZN3254 is built with a robust composite antenna and is ideal for harsh environments subject to temperature extremes and the elements. The integrated RF antenna harvests energy for the temperature sensing function, as well as communicates with a RAIN/UHF compliant reader. The integrated antenna is suitable for use on metal surfaces that might otherwise adversely affect wireless/RF communication range.

### Compliance




The AZN3254 is available in FCC and EU/ETSI frequency ranges. The AZN3254 requires a RAIN/UHF compliant reader. These sensors can be purchased separately or as part of a system.



## AZN3254 Performance Data

Rugged temperature sensor for on-metal and industrial applications

PARAMETER	VALUE
Normal temperature range	-40 °C to +85 °C
High-temperature alarm	Up to +125 °C
Compatible standards	EPC class 1 gen 2 v2.0.1 ISO 18000-6C
Integrated circuit	Powered by Magnus® S3
TID memory	64-bits
EPC memory	160-bits supporting up to 128-bit EPC
User memory	128-bits
Sensor Size	13.5 x 9.1 x 4.3 mm
Adhesive	Self-stick with easy release tab
Shipment method	Vacuum packed tray
Minimum order quantity	5 pc MOQ
Ordering information	RFM3254-AFS (FCC 902 to 928 MHz) RFM3254-AES (ETSI 865.6 MHz to 867.6MHz)



©2021 Axzon, Inc. All rights reserved. Reproduction in part or in whole is prohibited without prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. This product is covered by U.S. patents 7586385, 8081043 and other Axzon's granted and pending patents. Visit the Axzon website (<https://axzon.com/patents/>) for latest patent information. Chameleon™ and Magnus® are trademarks of Axzon, Inc. as well as the product and service names mentioned herein are registered trademarks of Axzon, Inc. All other trademarks are the property of their respective owners, Axzon, Austin Texas, USA.