




R3101CU

# Lepton<sup>3</sup>x1-USB

25dBm 1-Port USB  
RAIN RFID Reader Module



<b>BENEFITS</b>	Ultra compact size	High Sensitivity	USB Type-C connector	IOIO Serial interface	MMCX antenna connector	Wide voltage range
-----------------	--------------------	------------------	----------------------	-----------------------	------------------------	--------------------

## Features

- RAIN RFID (UHF EPC Class1 Gen2, ISO 18000-63) compliant
- Multiregional support
- Ultra compact size
- Up to 25 dBm (316 mW) output power
- USB Type-C interface (Virtual COM)
- Low power consumption

## Applications

- Handheld devices
- Multiregional label printers and applicators
- Points of sale readers
- Voice operated gloves
- Smart appliances for home automation
- Security and access management systems

## Overview

The **Lepton<sup>3</sup>x1-USB** (Model R3101CU), an embedded reader of the easy2read<sup>®</sup> product line, is an ultra compact reader for low power, high performance RAIN RFID applications.

With programmable output power from 10 dBm to 25 dBm, the reader can detect tags at more than 2 m of distance (depending on antenna and tag dimensions).


Due to its low power consumption, the module is specifically designed to be easily integrated in battery powered devices.

The radio frequency core of the module is based on the **Impinj E310** IC that permits to achieve fast reading speed and to be used in dense reader and dense tag environments for top-class rated performances.

The compactness of the device allows to embed the **Lepton<sup>3</sup>x1-USB** inside industrial handhelds, smartphone accessories and other compact form factor devices.

The **Lepton<sup>3</sup>x1-USB** complies with and can operate in both European and US regulatory environments and, thanks to its multiregional capabilities, it's ideal for integration in devices requiring compliance to different geographical regions.

The **Lepton<sup>3</sup>x1-USB** is designed on the basis of the **Lepton<sup>3</sup>** with the aim to facilitate the integration for those who prefer to use connectors instead of automatic manufacturing required by the SMD form factor.



## Technical Specification Table

<b>Frequency Range</b>	<ul style="list-style-type: none"> <li>• 865.600÷867.600 MHz (ETSI EN 302 208 v. 3.3.1)</li> <li>• 902÷928 MHz (FCC part 15.247)</li> </ul>
<b>RF Power</b>	Configurable from 0 dBm to 25 dBm (from 1 mW to 316 mW) conducted power
<b>RX Sensitivity</b>	• -72 dBm - 10%PER, assuming 20 dB antenna RL @ 25 dBm output
<b>Antenna VSWR Requir.</b>	< 2:1 for optimal performance
<b>Antenna Connectors</b>	MMCX jack
<b>Frequency Tolerance</b>	± 10 ppm over the entire temperature range
<b>Number of Channels</b>	<ul style="list-style-type: none"> <li>• 4 channels (compliant to ETSI EN 302 208 v. 3.3.1)</li> <li>• 50 hopping channels (compliant to FCC part 15.247)</li> </ul>
<b>Standard Compliance</b>	EPC Class 1 Gen 2 - ISO18000-63
<b>Connectivity</b>	<ul style="list-style-type: none"> <li>• USB Type-C Virtual COM Port</li> <li>• Communication parameters: <ul style="list-style-type: none"> <li>• Baudrate from 9.6 to 921.6 kbps, default 921.6 kbps</li> <li>• Databits: 8</li> <li>• Stopbit: 1</li> <li>• Parity: none</li> <li>• Flow control: none</li> </ul> </li> <li>• 3.3 V I/O voltage level</li> </ul>
<b>I/O Interface</b>	<ul style="list-style-type: none"> <li>• 4 I/O lines 3.3 V level</li> <li>• Iout = 8 mA max.</li> </ul>
<b>Power Supply</b>	• 4.75 ÷ 5.25 V DC (Model R3101CU)
<b>Power Consumption</b>	<ul style="list-style-type: none"> <li>• 800 mA @ 5 V - RF out = 25 dBm</li> <li>• 5 mA in idle mode - Ready to receive commands</li> </ul>
<b>Dimensions</b>	• (L)61 x (W)42 x (H)9.1 mm <sup>3</sup> /2.40 x 1.65 x 0.36 inches <sup>3</sup>
<b>Operating Temperature</b>	-20 °C to +70 °C
<b>Weight</b>	30 g

## Ordering Options

<b>WR3101CUXAAA</b>	Lepton3x1-USB - 25dBm Reader Mod.		

