

# PRODUCT DATASHEET

## Confidex Steelwave Micro II™ NFC



Small-sized NFC asset tag with versatile attachment options.

### ELECTRICAL SPECIFICATION

**Device type**

NFC Forum Type 2

**Air interface protocol**

ISO 14443A

**Operational frequency**

13,56 MHz

**IC type**

NXP NTAG213

**Memory configuration**

User memory 144 Bytes

**Read range\***

Mobile phone up to 30mm

Fixed reader up to 40mm

**Applicable surface materials\***

Works on any material

\* Read ranges are measured in laboratory environment and there can be some variation in real application. Also used surface material might affect the read range.

### MECHANICAL SPECIFICATION

**Tag materials**

Engineering plastics and synthetic face layer

**Background adhesive**

High performance acrylic adhesive

**Weight**

2 g

**Delivery format**


Single

**Amount in box**

1000pcs

**Dimensions**

38 x 13 x 4,5 mm / 1.5 x 0.5 x 0.17 in



### ENVIRONMENTAL RESISTANCE

**Operating temperature**

-20°C to +70°C / -4°F to +158°F

**Ambient temperature**

-20°C to +70°C / -4°F to +158°F

**IP classification**

IP67

**Chemical resistance**

No physical or performance changes in:

- 2 hour Salt water (salinity 10%) exposure

- 2 hour Motor oil exposure

Additionally, short time exposure resistant against sulfuric acid. Acetone and sodium hydroxide should be avoided.

**Expected lifetime**

Years in normal operating conditions

*Values in the table are the best recommendations; resistance against environmental conditions depends on the combination of all influencing factors, exposure duration and chemical concentrations. Thus, product's final suitability for certain environmental conditions is recommended to be tested. Contact Confidex for more specific information.*

## PERSONALIZATION OPTIONS

### Pre-encoding

- Customer specific encoding.

### Customized data label

- Customer specific layout including logo, text, numbers, barcodes etc.

## INSTALLATION INSTRUCTIONS

Steelwave Micro II can be attached with several fixing methods:

- High performance acrylic adhesive (included)
- Hanging with tethering string
- Cable tie through the tag

When mounting the tag with its adhesive background, clean and dry the surface for obtaining the maximum bond strength.

Ideal application temperature is from +21°C to +38°C (+70°F to +100°F), bond strength can be improved with firm application pressure and moderate heating from +38°C to +54°C (+100°F to +130°F).

Installation at temperatures below 10°C (50°F) is not recommended.

## ORDER INFORMATION

**Product number:** 3001301

**Product name:** Confidex Steelwave Micro II™ NFC NTAG213

For other versions, additional information and technical support contact Confidex Ltd.

### DISCLAIMER

THE MATERIALS, PRODUCTS AND SERVICES ARE SOLD SUBJECT TO ITS STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, CONFIDEX MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. EXCEPT AS PROVIDED IN CONFIDEX STANDARD CONDITIONS OF SALE, CONFIDEX AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS OR SERVICES DESCRIBED HEREIN.

Each user bears full responsibility for making its own determination as to the suitability of Confidex products, materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished systems incorporating Confidex products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Confidex.