



# TACEOS

### Datasheet



EOS-430 M830 global inlay combines moderate size with outstanding robust performance on a wide range of surfaces. This inlay is the product of choice for a wide range of applications such as retail, food and quick service restaurants, as well as logistics and general industrial segments. Hence, it is ideally suited for inventory visibility and item-level tagging.

EOS-430 is based on Impinj's M830 RAIN RFID IC with 128-bit EPC memory. The IC combines improved read sensitivity (-1.5 dB, compared to M730), AutoTune<sup>TM</sup> performance, and backscatter efficiency with a size reduction to support Tageos' sustainability approach. As a result, the IC sets standards in solutions like high-speed inventory counting, loss prevention with frictionless self-checkout, and embedded tagging with seamless product returns.



EOS-430 M830 is available in dry, wet, and paperface delivery formats.

Tageos was one of the first companies to qualify for ARC Quality Certification for its manufacturing operations from Auburn University RFID Lab. EOS-430 M830 complies with ARC specifications F, I, L, O, Q, R, Y2, W5 and W6.

Like all Tageos' RFID products, EOS-430 M830 complies with ISO 9001:2015 Quality Management System and ISO 14001:2015 Environmental Management System as well as Environmental Directives RoHS and REACH, utilizing sustainable materials such as FSC® certified paper whenever possible.

### Overview

IC: Impinj M830 EPC/User Memory: 128 bit /- bit

TID Memory: 96 bit incl. 48 bit unique S/N

Frequency Band: 860 - 960 MHz
Protocol: EPC Class 1 Gen 2 - ISO 18000-6c

#### **Application Areas**

- Apparel
- Inventory Visibility
- Item Level Tagging
- Logistics
- Supply Chain Management







# TACEOS

#### **Technical Overview**

	Dry	Wet	Paper-face
Product Code	430000075	430000076	430000077
Antenna Size	70 x 8 mm	70 x 8 mm	70 x 8 mm
	2.76 x 0.31 in	2.76 x 0.31 in	2.76 x 0.31 in
Finish Size	-	74 x 12 mm	74 x 12 mm
	-	2.91 x 0.47 in	2.91 x 0.47 in
Web Width	80.00 ± 1 mm	80.00 ± 1 mm	80.00 ± 1 mm
	3.150 ± 0.04 in	3.150 ± 0.04 in	3.150 ± 0.04 in
Pitch	16.00 ± 0.2 mm	16.00 ± 1 mm	16.00 ± 1 mm
	0.630 ± 0.01 in	0.630 ± 0.04 in	0.630 ± 0.04 in
ARC Approvals	F, I, L, O, Q, R, Y2, W5, W6	F, I, L, O, Q, R, Y2, W5, W6	F, I, L, O, Q, R, Y2, W5, W6
FSC® Certifi cation	-	-	-
Antenna Material	Aluminium	Aluminium	Aluminium
Front Face	-	PET clear	Paper TT
Inlay Substrate	PET Clear	PET Clear	PET Clear
Inlay Adhesive	-	permanent	permanent
Liner	-	Paper	Paper
Operating Temperature	-40°C / +85°C   -40°F / +185°F	-40°C / +85°C   -40°F / +185°F	-40°C / +85°C   -40°F / +185°F
	@20% to 90% RH	@20% to 90% RH	@20% to 90% RH
Shelf Life Time	2 years @ +25°C/40%RH	2 years @ +25°C/40%RH	2 years @ +25°C/40%RH
Final Inspection	100% tested	100% tested	100% tested







Tageos SAS (HQ) . 1340 rue de Pinville . 34000 Montpellier . France . sales@tageos.com



Graphs: All the graphs are indicative: performance in real life applications may vary. The data has been determined based on calculations for transmitters with a normal output power level and respective IC silicon. Storage & handling precautions: Observe standard storage and handling practices to minimize Electro Static Discharge. Tageos reserves the right to change its products and services at any time without notice. As our products are used in circumstances beyond our control, we cannot be held liable for any damages caused through their use. This is a general purpose product not designed or intended for any specific application.

© 2023 Tageos All rights reserved. The pictures and illustrations found on this document are for illustration purposes only, and do not necessarily represent the exact products. Tageos is a registered trademark. All other trademarks are the property of their respective owners. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use.


02/OCT/2024 tageos.com



### TAGEOS

### **Product Specifications**

#### **Mechanical Dimensions**



00077
mm / 2.76 x 0.31 in
mm / 2.91 x 0.47 in
1 mm / 3.150 ± 0.04 in
1 mm / 0.630 ± 0.04 in
mm / 0.079 ± 0.04 in
mm / 0.118 ± 0.04 in
ım / 0.236 in

02/OCT/2024 tageos.com



## TACEOS

### **Packing Details**

	Dry	Wet	Paper-face
Product Code	4300000075	430000076	4300000077
Delivery Format	Roll (single row)	Roll (single row)	Roll (single row)
Core Inner Diameter	76 mm / 2.99 in	76 mm / 2.99 in	76 mm / 2.99 in
Roll Outer Diameter	291 mm / 11.46 in	351 mm / 13.82 in	179 mm / 7.05 in
Unwinding Direction	Inlay on outside of roll	Inlay on outside of roll	Inlay on outside of roll
Standard Roll Size	38 000 (-0% +1.5%)	33 000 (-0% +1.5%)	5 000 (-0% +1.5%)
Min. Guar. Yield/Roll	99%	99%	99%
Box Dimensions	39.5 x 39.0 x 17.0 cm /	39.5 x 39.0 x 17.0 cm /	26.0 x 26.0 x 37.0 cm /
	15.56 x 15.35 x 6.69 in	15.56 x 15.35 x 6.69 in	10.24 x 10.24 x 14.57 in
Roll/Box	1	1	4
Inlays/Box	38 000	33 000	20 000
Box Gross Weight	6.07 kg / 13.38 lbs	8.48 kg / 18.70 lbs	7.21 kg / 15.90 lbs
Pallet Dimensions	120 x 80 x 151 cm /	120 x 80 x 151 cm /	120 x 80 x 126 cm /
	47.2 x 31.5 x 59.4 in	47.2 x 31.5 x 59.4 in	47.2 x 31.5 x 49.6 in
Boxes/Pallet	48	48	36
Inlays/Pallet	1824 000	1 584 000	720 000
Pallet Gross Weight	316 kg / 697 lbs	432 kg / 952 lbs	285 kg / 628 lbs

#### Contact:

Tageos SAS (HQ) . 1340 rue de Pinville . 34000 Montpellier . France . sales@tageos.com



© 2023 Tageos All rights reserved. The pictures and illustrations found on this document are for illustration purposes only, and do not necessarily represent the exact products. Tageos is a registered trademark. All other trademarks are the property of their respective owners. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use.

02/OCT/2024 tageos.com